



DT330-32 Button

## UNIVERGE® Desktop Digital Terminals

Fulfilling the promise of UNIVERGE®360

### At a Glance

- Scalability and customization through
  - modularity
- Bluetooth interface for peripheral
  - equipment (mobile phones, PDAs, headsets, conference units or keyboards)
- Programmable line keys for immediate
  - line/features access or speed dialing
- Full Duplex Speaker (DT330)

### Maximizing Productivity

In today's intensely competitive business environment, smart companies know that it takes great customer service to get ahead.

UNIVERGE Desktop Digital Terminals offer features and benefits that brilliantly capture the essence of form and function while providing businesses the means to seamlessly communicate with their customers. These intelligent terminals help your business take service and performance to newer, more profitable heights.

Desktop Digital terminals deliver exceptional value. With their user-friendly ergonomic design, a range of four models to choose from and a choice of interfaces and options, they provide users with access to the full power of UNIVERGE communication platforms.



Features		DT330	DT310
Display	Display Size	168×58 dot matrix grayscale Optional LCD backlit Optional DESI-less display	6D: 168×41 dot matrix grayscale LCD no backlit
	Characters × Lines	Alphanumeric: 28×4 (6×12 font) DESI-less: 28×4 (6×12 font)	6D: 24×3
	Tilttable	Yes	N/A
Keypad	Backlit Keypad	Yes	N/A
	Line Keys	12, 24, 32 DESI-less: 8×4 pages	2, 6
	Softkeys	4, help, exit	4, help, exit
	Cursor Keys	Yes	2D: N/A, 6D: Yes
Built In Applications	Personal Directory	Yes	Yes
	System Directory	Yes	N/A
	Corporate Directory	Yes	N/A
	Call History	Yes	Yes
Sound	Full duplex hands-free	Yes	No
Optional Adapters	Bluetooth Hub	Yes	N/A
	Bluetooth Handset	Yes	N/A
	Recording Adapter	Yes	N/A
	Analog Port Adapter w/Ringer	Yes	N/A
	PSTN Survivable Adapter	Yes	N/A
Characteristics	Dimension (w×d×h) cm	12D/24D: 17.91×25.81×11.20 32D (24D+8LK): 21.11×25.81×11.20 DESI-less: 17.91×27.20×11.20	2D: 17.91×22.50×11.20 6D: 17.91×22.50×11.20
	Weight (approx. kg.)	12D/24D: 1.0 32D (24D+8LK): 1.2 DESI-less: 1.1	2D: 0.9 6D: 0.9
	AC Adapter (optional)	27V 750mA	
Standards	Electrical	R&TTE EN55024 EN55022 Class B	
	RoHS	All models comply with RoHS	
	Safety	EN60950/IEC60950	
	UL/CSA	FCC Part 15 Class B FCC Part 68	
Environmentals	Operating Conditions	Temperature range: 0 to 40°C, humidity: 10 to 90% RH (not condensing)	
	Storage	Ambient temperature range: -20 to 60°C, ambient humidity: 10 to 90% RH	

UNIVERGE360 is NEC's approach to unifying business communication. It places people at the center of communications and delivers on an organization's needs by uniting infrastructure, communications and business.

Empowered by Innovation **NEC**

NEC Infrontia Asia Pacific Sdn Bhd  
[www.necinfrontia-ap.com](http://www.necinfrontia-ap.com)

NEC Asia Pte Ltd  
[www.nec.com.sg](http://www.nec.com.sg)

NEC Corporation (Thailand) Ltd  
[www.nec.com.th](http://www.nec.com.th)

NEC Corporation of Malaysia Sdn Bhd  
[www.necmalaysia.com.my](http://www.necmalaysia.com.my)

NEC India Pvt Ltd  
[www.necindia.in](http://www.necindia.in)

NEC Philippines Inc.  
[www.nec.com.ph](http://www.nec.com.ph)

This Publication provides outline information only which (unless specifically agreed to by NEC INFRONTIA in writing) may not be used, applied, or reproduced for any purpose or form part of any order or contact or be regarded as a representation relating to the products or services concerned. NEC INFRONTIA reserves the right to alter without notice the specification, design, price or conditions of supply of any products or service. Models, functions, features and options may vary for each country. NEC Infrontia reserves the right to announce or not to announce certain models, functions, features and options in the regions.

© 2008 NEC Corporation. All rights reserved. NEC, the NEC logo, UNIVERGE and the UNIVERGE logo are trademarks of NEC Corporation in Japan, and other countries, or both. All trademarks identified with ® or ™ are registered trademarks or trademarks respectively. Please refer to your local NEC representatives for further details.